

Product Highlights

Wi-Fi 7 Dual-Band Performance

Powered by Wi-Fi 7 dual-band 2×2 + 2×2, the AP delivers stable, efficient connectivity for everyday business use. Ideal for office and basic commercial deployments as a practical entry-level solution.

Flexible Connectivity and Power

2.5G Ethernet PoE port transmits data and power over one cable, simplifying installation and reducing costs for SMBs.

Enterprise Design

Multiple SSIDs, VLANs, and advanced wireless security help provide a stable, secure, and scalable network in offices, campuses, and commercial environments.



DAP-E3620

BE3600 Wi-Fi 7 Ceiling Mount Access Point

Key Features

Wi-Fi 7 Technology

- Wi-Fi 7 2x2 + 2x2 dual-band BE3600 solution
- Multi-Link Operation (MLO) improves transmission efficiency and connection stability
- 4096-QAM modulation enhances data throughput and spectrum efficiency

Customisable Captive Portal

- Each SSID can be configured with a dedicated captive portal page
- Customisable login pages for branding, advertising, or promotional purposes

Central Management

- Supports Nuclias Unity, Nuclias hardware controller, and Nuclias software controller for centralised management, monitoring, and maintenance
- Provides flexible deployment options with centralised cloud or on-premises management

Advanced Security

- Latest WPA3 Personal/Enterprise encryption
- Supports 802.1x and MAC/IP ACL
- Establish complete security protection for wireless network

VLAN Per SSID

- Each SSID can have a different VLAN tag
- One EAP can serve different user groups for users and access control for each group

The DAP-E3620 BE3600 Wi-Fi 7 Ceiling Mount Access Point is designed for everyday networking needs in general business and commercial environments, delivering reliable, stable, and secure wireless connectivity. With Wi-Fi 7 dual-band technology, advanced security features, and centralised management, it effectively meets the wireless requirements of offices and basic commercial spaces.

Wi-Fi 7 Connectivity

The DAP-E3620 leverages core Wi-Fi 7 technologies such as Multi-Link Operation (MLO) and 4K QAM, enabling dynamic traffic allocation across multiple frequency bands to improve performance, reduce latency, and increase overall network capacity.

2.5-Gigabit Ethernet Port

The DAP-E3620 also provides fast wired connectivity, effectively reducing network latency and ensuring reliable performance for bandwidth-demanding applications. With support for 2.5 GbE speeds, it delivers a stable and efficient wired network experience, ideal for everyday office and business use.

Powered by PoE

The DAP-E3620 can be powered directly via a PoE switch, enabling flexible installation without the need for additional power outlets. This simplifies deployment and reduces overall installation costs, making network expansion more efficient and cost-effective.

SSID-VLAN Mapping

The DAP-E3620 supports SSID-VLAN Mapping, allowing administrators to assign different SSIDs to specific VLAN tags. This capability effectively segregates user group access without compromising network security, ensuring traffic isolation and enhancing overall network management.

Customisable Captive Portal

The DAP-E3620 offers a customisable Captive Portal, enabling network administrators to create personalised login pages. This not only enhances network security through proper user authentication but also strengthens user engagement with tailored branding and messaging.

DAP-E3620 BE3600 Wi-Fi 7 Ceiling Mount Access Point

Advanced Security

The DAP-E3620 delivers Advanced Security features, including the latest WPA3™ Personal and Enterprise encryption and MAC/IP Access Control Lists (ACLs). These robust security measures ensure networks with higher security requirements are well protected against unauthorised access and potential threats.


Multiple Operational Modes

The DAP-E3620 offers Multiple Operational Modes to accommodate diverse deployment scenarios. In addition to standard AP mode, it supports WDS and WDS+AP modes, providing flexible options for extending network coverage and integrating with existing infrastructure.

Centralised Management

The DAP-E3620 supports Nuclias Unity, as well as Nuclias hardware and software controllers, enabling centralised management, monitoring, and maintenance. Users can easily automate, monitor, and scale their network operations through an intuitive interface and real-time data insights. It provides flexible deployment options with centralised cloud or on-premises management, making network administration simpler and allowing seamless expansion as the network grows. Centralised management ensures optimal performance and security while saving time and improving efficiency.

Connection Diagram



DAP-E3620 BE3600 Wi-Fi 7 Ceiling Mount Access Point

Specifications

General
Device Interfaces
1 x 2.5 Gigabit Ethernet PoE LAN port 1 x Power input connector 1 x Reset button
LED
Power/Status
Antenna
2 x 4 dBi @ 2.4 GHz 2 x 4 dBi @ 5 GHz
Wi-Fi Data Rate ^{2,3}
2.4 GHz up to 688 Mbps 5 GHz up to 2882 Mbps
IEEE Standard ³
- IEEE 802.11be/ax/ac/n/g/b/a - IEEE 802.3t PoE - IEEE 802.3u/ab/an/bz - IEEE 802.3az Energy-Efficient Ethernet (EEE)
Maximum Output Power ¹
24 dBm (2.4 GHz) 23 dBm (5 GHz)
Functionality
Security Protocol
- WPA/WPA2/WPA3™ Personal/Enterprise - SSID broadcast disable - MAC address access control - WEP 64/128-bit - Enhanced Open - Internal RADIUS server
Operating Frequency ²
2.4 - 2.483 GHz 5.15 - 5.85 GHz
Software
Device Management
- Web (HTTP/HTTPS) - Nuclias Unity - Nuclias hardware and software controller - Telnet/SSH - SNMP

Physical
Dimensions
186 x 186 x 37 mm
Weight
550 g
Power Input
802.3at or 12V/2A
Max Power Consumption
< 20W
Operating Temperature
0 to 40 °C
Storage Temperature
-20 to 65 °C
Operating Humidity
10% to 90% non-condensing
Storage Humidity
5% to 95% non-condensing
Certifications ⁴
CE
Ordering Information
DAP-E3620
BE3600 Wi-Fi 7 Ceiling Mount Access Point
Package Contents
- DAP-E3620 - Mounting Plate - Quick Start Guide

1. The maximum output power is the board limit value, the actual output power will depend on regulatory requirements.

2. Maximum wireless signal rate derived from IEEE standard 802.11 and 802.11ax specifications. Actual data throughput will vary. Network conditions and environmental factors, including volume of network traffic, building materials, construction, and network overhead may lower actual data throughput rate. Environmental factors will adversely affect wireless signal range.

3. Please note that operating frequency ranges vary depending on the regulations of individual countries and jurisdictions. The DAP-E3620 may not support the 5.25 - 5.35 GHz and 5.47 - 5.725 GHz frequency ranges in certain regions.

4. For the EU region, this product is compliant with CE regulations and operates within the following frequency ranges: 2.4 - 2.4835 GHz, 5.150 - 5.250 GHz, 5.250 - 5.350 GHz, and 5.470 - 5.750 GHz

Actual performances may vary due to settings, cabling, temperature, network configuration, interface, device compatibility, environmental and on-site conditions, and other similar factors. References to power capability, signal or processing speed, signal range or distance, data encryption, storage capacity, display properties, or other performance metrics are based on optimal conditions derived from industry standards and provided for informational purposes only. Specifications may be subject to change without prior notice.